



## IP Outdoor AutoFocus 4MP Dome Camera with Advanced Analytics

**AUTO**  
DISCOVER  
CONFIGURE

OUTDOOR/  
INDOOR

**DOME**  
CAMERA

**AUTO**  
FOCUS

**4MP**

ADVANCED  
ANALYTICS

### Adaptable Coverage for Any Install.

The ELAN EL-IP-ODA4, available in White or Black, is a versatile 4MP dome camera with autofocus and advanced object analytics that's ideally suited to both residential and commercial installations. It's an ideal choice for outdoor or indoor spaces requiring the ability to watch a wide area with autofocus convenience and speed. This camera can cover a large backyard deck and a gate 50 feet away.

This dome camera is quick and easy to install, and its auto-focus feature enables final focus adjustment from within the ELAN App (rather than up on a ladder). The dome camera form factor is intended for ceiling mount.

#### Video Analytics

Advanced Object Detection, Person and Vehicle Classification greatly reduce false positive alerts. Push Messages can be dispatched to a mobile device to alert user of detected events.

#### Auto-Discover/Auto-Configure

Like all other ELAN Surveillance products, the EL-IP-ODA4 is embedded with the ELAN beacon, making it simple and easy to install in any ELAN system.

The ELAN Management Cloud or Configurator scans the network – both wired and wireless – and automatically discovers the SSIDs of available devices. With a click, the camera is configured and installed in the ELAN system. We've eliminated the need for a secondary application to setup the camera outside of ELAN, saving substantial time on every project.

#### Comprehensive Surveillance

ELAN Surveillance cameras work seamlessly with the ELAN Network Video Recorder (EL-NVR Series) to create a surveillance ecosystem that excels in every way. Cameras and NVR can be fully managed from within the ELAN App, simplifying the customer experience and enhancing security overall.



One-click setup for integrators with ELAN Auto-Discover / Auto-Configure.

**IR**  
ILLUMINATION



Illumination from Infrared (IR) LEDs enables night vision up to 30 meters.

**ADVANCED**  
ANALYTICS



Advanced Object Detection, Person and Vehicle Classification.

**AUTO**  
FOCUS



Fine-tune the focus and zoom from within the ELAN app, rather than up on the ladder.

**WDR**



Wide Dynamic Range improves image quality by balancing dark and light areas in an image.

**FEATURES**

- Autofocus
- IntelliVision® Advanced Analytics
- Auto-Discover/Auto-Configure
- 4 Megapixel
- High Dynamic Range (HDR)
- 30m IR Distance
- 2.8mm-8mm Autofocus Lens
- Lens Distortion Correction
- Advanced Built-in Motion Analytics
- Micro SD Card Slot
- Alarm In/Out
- 2-Way Audio Support
- Automatic Gain Control (AGC)
- Max Frame Rate: 20FPS @ 2688x1520
- 3D Digital Noise Reduction
- 2D Wide Dynamic Range
- Power Over Ethernet (PoE)

**INCLUDED IN THE BOX:**

- (1) Camera
- (1) Quick Installation Guide
- (1) Mounting Template
- (3) Mounting Hardware
- (1) Allen Wrench
- (2) Phoenix Connectors

**SPECIFICATIONS**

Power Consumption	DC12V, 7.4W / PoE, 9W
Dimensions	4.72" x 4.17"
Weight	15.3oz
Operating Temperature	-40°F – 122°F
Focal Length	2.8 – 8 mm (zoom / focus motorized)
IR Range	30m
Alarm Event Triggers	Motion/Tamper/Network lost detection
Alarm Event Actions	FTP, SMTP, SAMBA
SD Card Recording	N/A
Video Analytics	Survey Area, Object Detection, Person Classification, Vehicle Classification
Certifications	CE: Class B, FCC: Class B, IP66 Weather Resistant

**VIDEO**

Video Compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Maximum Frame Rate	H.264 / Motion JPEG: up to 20 fps @ 2688x1520
Day/Night (IR-cut filter)	Color (Day), Monochrome (Night), Auto, Schedule
Scanning System	Progressive scan
Back Light Compensation	On / Off
2D WDR	Off / Auto / x2 / x3 / x4
High Dynamic Range (HDR)	Up to 100dB
3D Noise Reduction	Off / 1 to 32 selectable
Privacy Masking	Off / On (4 independent areas)
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	42 dB variable gain
Other Functions	Sharpness, Hue, Image flip, Image mirror
Lens Distortion Correction (LDC)	Yes

**NETWORK**

Ethernet	10Base-T / 100Base-TX, RJ-45
On-Screen Display (OSD)	Text over date, time, and camera name
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTP, Telnet, ICMP, IGMP, SDDP, Bonjour
Multi IP Addresses	Yes



Your world, made simple.™

[elancontrolsystems.com/](http://elancontrolsystems.com/)

# IP Outdoor AutoFocus Turret Camera with Advanced Analytics



One-click set-up with ELAN Auto-Discover/Auto-Configure




Illumination from Infrared (IR) LEDs enables night vision up to 30 meters



Advanced Object Detection, Person and Vehicle Classification



Fine-tune the focus from within the ELAN app, rather than up on the ladder



Wide Dynamic Range improves image quality by balancing dark and light areas in an image

## Auto-Focus and Advanced Analytics

The ELAN EL-IP-OTA4, available in White and Black, is a versatile 4MP turret camera with autofocus and advanced object analytics to elevate the intelligent home and business. It's the ideal choice for installations requiring enhanced information reporting, crystal clear images, IP66 weather resistance, and superior IR captures.

The EL-IP-OTA4 turret camera is quick and easy to install, and its auto-focus feature enables final focusing from within the ELAN App, rather than up on the ladder. The turret camera can be either ceiling-mounted or wall-mounted, expanding placement opportunities. The EL-IP-OTA4 camera has a flat lens, independent IR sensor for distortion-free images, plus superior IR capture with no IR bounce – all in an attractive housing.

### Video Analytics

Advanced Object Detection, Person and Vehicle Classification greatly reduces false positive alerts. And Push Messages can be easily set up to alert a user's mobile device of events around the home.

### Auto-Discover/Auto-Configure

Like all other ELAN Surveillance products, the EL-IP-OTA4 is embedded with the ELAN beacon, making it effortless to install in any ELAN system. The ELAN Management Cloud or Configurator scans the network – both wired and wireless – and automatically discovers the SSIDs of available devices. With a click, the camera is configured and installed in the ELAN system. We've eliminated the need to use a secondary application to setup the camera outside of ELAN, saving substantial time on every surveillance installation.

### Comprehensive Surveillance

ELAN Surveillance cameras work seamlessly with the ELAN Network Video Recorder (EL-NVR Series) to create a surveillance ecosystem that excels in every application. Cameras and NVR can be fully managed from within the ELAN App, simplifying the user experience.

**FEATURES**

- AutoFocus
- IntelliVision® Advanced Analytics
- Auto-Discover/Auto-Configure
- 4 Megapixel
- 30m IR Distance
- 2.8-8mm AutoFocus Lense
- Advanced Built-in Motion Analytics
- IP66 Weather Resistant
- Alarm In/Out
- 2-Way Audio Support
- Automatic Gain Control (AGC)
- Operating Temperature: -40°F – 122°F
- Max Frame Rate: 20FPS @ 2688x1520
- 3D Digital Noise Reduction
- 2D Wide Dynamic Range
- Power Over Ethernet (PoE)

**INCLUDED IN THE BOX:**

- (1) Camera
- (1) Quick Installation Guide
- (1) Mounting Template
- (3) Mounting Hardware
- (1) Allen Wrench

**SPECIFICATIONS**

Power Consumption	DC12V, 7.2W / PoE, 8.3W
Dimensions	4.5" x 3.58"
Weight	15.3oz
Operating Temperature	-40°F – 122°F
Focal Length	2.8 – 8 mm (zoom / focus motorized)
IR Range	30m
Alarm Event Triggers	Motion/Tamper/Network lost detection
Alarm Event Actions	FTP, SMTP, SAMBA
SD Card Recording	N/A
Video Analytics	Survey Area, Object Detection, Person Classification, Vehicle Classification
Certifications	CE: Class B, FCC: Class B, IP66 Weather Resistant

**VIDEO**

Video compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Maximum Frame Rate	H.264 and MJPEG: : up to 30 FPS @ 1920 x 1080
Day/Night (IR-cut filter)	Color (Day), Monochrome (Night), Auto, Schedule
Scanning system	Progressive scan
Back Light Compensation	On / Off
High Dynamic Range (HDR)	Up to 100db
2D WDR	Off / Auto / x2 / x3 / x4
3D Noise Reduction	Off / 1 to 32 selectable
Privacy Masking	Off / On (4 independent areas)
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	36 dB variable gain
Other Functions	Sharpness, Hue, Image flip, Image mirror
Lens Distortion Correction (LDC)	Yes

**NETWORK**

Ethernet	10Base-T / 100Base-TX, RJ-45
On-Screen Display (OSD)	Text over date, time, and camera name
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTP, Telnet, ICMP, IGMP, SDDP, Bonjour
Multi IP Addresses	Yes

**ELAN**

Your world, made simple.™

[elancontrolsystems.com](http://elancontrolsystems.com)



## IP Outdoor AutoFocus 4MP Bullet Cameras with Advanced Analytics

**AUTO**  
DISCOVER  
CONFIGURE

**BULLET**  
IC

**OUTDOOR/  
INDOOR**

**AUTO  
FOCUS**

**4MP**

**2MP**

### Outdoor Surveillance Redefined.

The ELAN EL-IP-OBA4, available in White or Black, is a versatile 4MP bullet camera with autofocus and advanced object analytics. The distinctive and recognizable bullet form factor can be an effective deterrent in places where you want people to know that they can be seen. It's ideal to survey a designated area such as a driveway, garage, stairway hallways and an entryway. Flexible in placement and easy to install, this camera can be installed on walls, soffits or under eaves. The autofocus feature enables final focus adjustment from within the ELAN App (rather than up on a ladder). The bullet camera has an adjustable lens shade to minimize glare.

#### Potent Video Analytics

Advanced Object Detection, Person and Vehicle Classification greatly reduce false positive alerts. Push Messages can be sent to a mobile device to alert user of detected events.

#### Auto-Discover/Auto-Configure

Like all other ELAN Surveillance products, the EL-IP-OBA4 is embedded with the ELAN beacon, making it fast and simple to install in any ELAN system. The ELAN Management Cloud or Configurator scans the network – both wired and wireless – and automatically discovers the SSIDs of available devices. With a click, the camera is configured and installed in the system. We've eliminated the need for a secondary application to setup the camera outside of ELAN, saving substantial time on every project.

#### Comprehensive Surveillance

ELAN Surveillance cameras work seamlessly with the ELAN Network Video Recorder (EL-NVR Series) to create a surveillance ecosystem that excels in every application. Cameras and the NVR can be managed from within the ELAN App, simplifying daily use and the experience.



One-click setup for integrators with  
ELAN Auto-Discover / Auto-Configure.

**IR**  
ILLUMINATION




Illumination from Infrared (IR) LEDs  
enables night vision up to 30 meters.



**AUTO  
FOCUS**

Fine-tune the focus and zoom from  
within the ELAN app, rather than  
up on the ladder.



**WDR**

Wide Dynamic Range improves image  
quality by balancing dark and light  
areas in an image.



**ADVANCED  
ANALYTICS**

Advanced Object Detection, Person  
and Vehicle Classification.



## FEATURES

- Autofocus
- IntelliVision® Advanced Analytics
- Auto-Discover/Auto-Configure
- 4 Megapixel
- High Dynamic Range (HDR)
- 30m IR Distance
- 2.8-8mm AutoFocus Lens
- Advanced Built-in Motion Analytics
- IP66 Weather Resistant
- Micro SD Card Slot
- Automatic Gain Control (AGC)
- Operating Temperature: -40°F – 122°F
- Max Frame Rate: 20fps @ 2688x1520
- 3D Digital Noise Reduction
- 2D Wide Dynamic Range
- Power Over Ethernet (PoE)

## INCLUDED IN THE BOX:

- (1) Camera
- (1) Quick Installation Guide
- (1) Mounting Template
- (3) Mounting Hardware

## SPECIFICATIONS

Power Consumption	DC12V, 7.5W / PoE, 8.6W
Dimensions	2.67"(W) x 2.71"(H) x 8.42"(D)
Weight	18.16oz
Operating Temperature	-40°F – 122°F
Focal Length	2.8 – 8 mm (zoom / focus motorized)
IR Range	30m
Alarm Event Triggers	Motion/Tamper/Network Lost Detection
Alarm Event Actions	FTP, SMTP, SAMBA
SD Card Recording	N/A
Video Analytics	Survey Area, Object Detection, Person Classification, Vehicle Classification
Certifications	CE: Class B, FCC: Class B, IP66 Weather Resistant

## VIDEO

Video compression	Smart H.264/ H.264 High/Main Profile, Motion JPEG
Maximum Frame Rate	H.264 / Motion JPEG: up to 20 fps @ 2688x1520
Day/Night (IR-cut filter)	Color (Day), Monochrome (Night), Auto, Schedule
Scanning system	Progressive Scan
Back Light Compensation	On / Off
2D WDR	Off / Auto / x2 / x3 / x4
High Dynamic Range (HDR)	Up to 100dB
3D Noise Reduction	Off / 1 to 32 selectable
Privacy Masking	Off / On (4 independent areas)
Sense Up	Off / 1 frame / 2 frames
Sense Up+	Yes
Auto Gain Control	36 dB variable gain
Other Functions	Sharpness, Hue, Image flip, Image mirror
Lens Distortion Correction (LDC)	Yes

## NETWORK

Ethernet	10Base-T / 100Base-TX, RJ-45
On-Screen Display (OSD)	Text over date, time, and camera name
Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, MQTT, QoS, SNMP, SNMP Trap, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, RTSP, RTCP, Telnet, ICMP, IGMP, SDDP, Bonjour
Multi IP Addresses	Yes



Your world, made simple.™

[elancontrolsystems.com](http://elancontrolsystems.com)