




P3 User Manual

Introduction

Thank you for purchasing the Fosi Audio P3 Tube Preamplifier!

The Fosi Audio P3 is a genuine tube preamp, with the tube working voltage reaching up to 54V. It features the QCC3031 Bluetooth chip, supporting aptX, aptX HD, and aptX LL audio formats, offering enhanced sound quality and as low as 40ms latency. The P3 comes with RCA out, AUX out, and a 3.5mm headphone jack, perfectly suited for your desktop use, delivering the ultimate auditory experience. The tubes are replaceable, adding to the fun of personalizing your setup. Combined with the glacier-colored light, it feels closer to nature. We believe that technology and nature can coexist harmoniously, and technological innovation can serve to enrich our lives.



- ① 3.5mm headphone jack
- ② Volume knob
- ③ Treble knob ($\pm 6\text{dB}$)
- ④ Bass knob ($\pm 12\text{dB}$)
- ⑤ Mode indicator light: RCA mode - steady red light, Bluetooth pairing mode - blue light flashing, Bluetooth connection successful - steady blue light
- ⑥ Power switch/mode selector
- ⑦ Bluetooth reset switch: Hold for 3 seconds to clear Bluetooth pairing
- ⑧ RCA input
- ⑨ RCA output
- ⑩ AUX output
- ⑪ DC 12V power in
- ⑫ Bluetooth antenna port
- ⑬ 5654W tubes


Specifications

RMS Power	250mw @16Ω; 150mw @32Ω; 32mw @250Ω; 20mW @300Ω
Headphone Impedance	16-300Ω
Input	Bluetooth, RCA
Output	RCA, 3.5mm headphone jack, AUX Out
SNR	≥103dB
Dynamic Range	104dB
THD	≤ 0.02%
Noise Floor	64uV
Crosstalk	95dB
Frequency Response	20Hz-20kHz(±1dB)
Bluetooth Chip	QCC3031
Bluetooth Version	5.1
Bluetooth Range	≥10m
Bluetooth Codecs	SBC/AAC/aptX/aptX HD/aptX LL
Power Input	DC 12V/1.5A~3A

Package Contents

Fosi Audio P3 Tube Preamplifier × 1 5654W Vacuum Tube × 2
12V/1.5A Power Supply × 1 User Manual × 1

Operation Guide



- 1.** Switch to the OFF position, install the Bluetooth antenna, and then plug the tubes to the sockets. Ensure the pins align with the slots, and then turn the volume to the lowest setting;
- 2.** Connect the included 12V/1.5A power supply;
- 3.** Depending on your setup, plug your amplifier, powered speakers, or headphones into the P3's RCA output, AUX output, or headphone jack;
- 4.** If you opt for a wired connection, use an audio cable to connect your source device to the P3's RCA input terminal;
- 5.** Switch to either the RCA wired or BT Bluetooth wireless position;
- 6.** When using Bluetooth, connect to Fosi Audio P3 on your source device;
- 7.** Adjust the volume and treble/bass to an appropriate level, and you're ready to enjoy your music.

Precautions

1. As a genuine tube preamplifier, please allow me 15 seconds to preheat the tubes after powering on, and then the sound can be output normally.
2. Avoid plugging and unplugging cables while the device is powered on to prevent abnormal noises. This can also easily damage the product.
3. If you need to replace the tubes, please do so when the tubes have cooled down to avoid burns or damage to the product.

Frequently Asked Questions

1. After connecting the product and turning it on, there's no sound during playback?

Since the P3 is a tube preamp, the tubes require about 15 seconds to preheat before they can operate properly. If there is still no sound after 15 seconds, please check if the cables are connected correctly, if the tubes are properly plugged, and if the correct input mode is selected.

2. Why is the power indicator light very dim or constantly flashing after powering on?

A blinking blue light in Bluetooth mode indicates it's awaiting a connection, and the light will remain steady blue once connected. A flashing power indicator light in RCA mode might suggest insufficient power supply. Please ensure you're using a power supply between 12V/1.5A and 12V/3A.

3. How are the headphone output, RCA output, and AUX output on the Fosi Audio P3 controlled?

By default, Fosi Audio P3 prioritizes headphone output, with RCA and AUX outputting simultaneously. This means both RCA and AUX will output signals at the same time; however, when a headphone is plugged in, the signal will switch to the headphone output, and there will be no signal on RCA and AUX outputs.

4. How do I clear the Bluetooth pairing record?

On the rear panel of the Fosi Audio P3, there's an RST button. Press and hold for 3 seconds to clear Bluetooth pairing. If you're in Bluetooth mode at this time, the indicator light will flash blue.

If you have any further questions, please contact our support team at support@fosiaudio.com

Warranty and Maintenance

Fosi Audio pledges to give a 24-month limited warranty and support from the date of purchase. If you encounter any problem when using our product, please contact our support team at support@fosiaudio.com.

About Us

Fosi Audio designs and builds innovative audio products with all your music in mind. Great sound, simple but elegant designs, high-quality components, and truly useful features are what Fosi Audio pursues. We sincerely hope you can get as much enjoyment from our products as we've had to create them!

Our Website: www.fosiaudio.com

Amazon Store: www.amazon.com/fosiaudio

Facebook Page: Fosi Audio

Youtube Channel: Fosi Audio

Whatsapp: +86 13716612254

After-Sales Service and Technical Support Email:

support@fosiaudio.com



Get online support