



COMPOSER

We designed the Composer Collection as the perfect match for our Director Collection. Across each model, the levels of performance remain consistent. This unity allows you to timbre match our in-wall and in-ceiling models with confidence.

Form and Function.

In-wall loudspeakers are perfect for ear level applications, such as home theatre or music listening. To make installation easier, all models (except the CIW series) have spring-loaded dog-ears that snap into place with just a quick turn from a coin or the included guitar-pick.



We've crafted different styles of in-wall to suit any need you might have.

THTR SPEAKERS

The THTR loudspeakers are for high-volume, high-demand applications. Use two for your left and right channels alongside a television or projector screen. Even add a third for your centre channel for even more impact.

LCR SPEAKERS

Left, centre, right. This configuration is also an excellent choice for home theatre when the volume isn't as critical of an issue.

THINLINE SPEAKERS

Based on the golden ratio, these loudspeakers are taller and thinner than the standard in-wall design. By using rectangular woofers, we are better able to match the modern aesthetic of flatscreen panels.

COMPOSER COLLECTION



THTR69

Part: SWML230900
Woofer: (4) Quad: 6 ½" Kevlar®
Tweeter: 1" Silk DPSD™
Power RMS: 50 Watts
Power Peak: 200 Watts
Frequency Response: 40Hz-20kHz
Impedance : 6 ohm
Dimensions: 219 x 758mm
Cutout Dimensions: 200 x 736mm
Grille Dimensions: 231 x 769mm
Mounting Depth: 95mm



THTR67

Part: SWML230700
Woofer: (4) Quad 6 ½" Glass Fibre
Tweeter: 1" Silk DPSD™
Power RMS: 50 Watts
Power Peak: 200 Watts
Frequency Response: 40Hz-20kHz
Impedance : 6 ohm
Dimensions: 219 x 758mm
Cutout Dimensions: 200 x 736mm
Grille Dimensions: 231 x 769mm
Mounting Depth: 95mm



LCR69

Part: SWML14900
Woofer: 2 x 6 ½" Kevlar®
Tweeter: 1" Silk DPSD™
Power RMS: 40 Watts
Power Peak: 150 Watts
Frequency Response: 51Hz-20kHz
Impedance : 6 ohm
Dimensions: 190 x 386mm
Cutout Dimensions: 168 x 364mm
Grille Dimensions: 200 x 396mm
Mounting Depth: 95mm



LCR67

Part: SWML14700
Woofer: 2 x 6 ½" Glass Fibre
Tweeter: 1" Silk DPSD™
Power RMS: 40 Watts
Power Peak: 150 Watts
Frequency Response: 53Hz-20kHz
Impedance : 6 ohm
Dimensions: 190 x 386mm
Cutout Dimensions: 168 x 364mm
Grille Dimensions: 200 x 396mm
Mounting Depth: 95mm



LCR65

Part: SWML14500
Woofer: 2 x 6 ½" IMG
Tweeter: 1" Silk DPSD™
Power RMS: 40 Watts
Power Peak: 150 Watts
Frequency Response: 55Hz-20kHz
Impedance : 6 ohm
Dimensions: 190 x 386mm
Cutout Dimensions: 168 x 364mm
Grille Dimensions: 200 x 396mm
Mounting Depth: 95mm



LCR39

Part: SWML10900
Woofer: 2 x 3 ½" Kevlar®
Tweeter: 1" Silk DPSD™
Power RMS: 35 Watts
Power Peak: 125 Watts
Frequency Response: 70Hz-20kHz
Impedance : 6 ohm
Dimensions: 134 x 262mm
Cutout Dimensions: 112 x 240mm
Grille Dimensions: 144 x 272mm
Mounting Depth: 95mm



LCR37

Part: SWML10700
 Woofer: 2 x 3 ½" Glass Fibre
 Tweeter: 1" Silk DPSD™
 Power RMS: 35 Watts
 Power Peak: 125 Watts
 Frequency Response: 70Hz-20kHz
 Impedance : 6 ohm
 Dimensions: 134 x 262mm
 Cutout Dimensions: 112 x 240mm
 Grille Dimensions: 144 x 272mm
 Mounting Depth: 95mm



C69

Part: SWM12900
 Woofer: 4 x 8" Kevlar®
 Tweeter: 1" Silk DPSD™
 Power RMS: 50 Watts
 Power Peak: 125 Watts
 Frequency Response: 40Hz-20kHz
 Impedance : 6 ohm
 Dimensions: 140 x 300mm
 Cutout Dimensions: 118 x 278mm
 Grille Dimensions: 149 x 311mm
 Mounting Depth: 95mm



C67

Part: SWM12700
 Woofer: 4 x 8" Glass Fibre
 Tweeter: 1" Silk DPSD™
 Power RMS: 50 Watts
 Power Peak: 125 Watts
 Frequency Response: 43Hz-20kHz
 Impedance : 6 ohm
 Dimensions: 140 x 300mm
 Cutout Dimensions: 118 x 278mm
 Grille Dimensions: 149 x 311mm
 Mounting Depth: 95mm



C65

Part: SWM12500
 Woofer: 4 x 8" IMG
 Tweeter: 1" Silk DPSD™
 Power RMS: 50 Watts
 Power Peak: 125 Watts
 Frequency Response: 45Hz-20kHz
 Impedance : 6 ohm
 Dimensions: 140 x 300mm
 Cutout Dimensions: 118 x 278mm
 Grille Dimensions: 149 x 311mm
 Mounting Depth: 95mm



C63

Part: SWM12300
 Woofer: 4 x 8" Poly
 Tweeter: 1" Aluminum
 Power RMS: 50 Watts
 Power Peak: 125 Watts
 Frequency Response: 45Hz-20kHz
 Impedance : 6 ohm
 Dimensions: 140 x 300mm
 Cutout Dimensions: 118 x 278mm
 Grille Dimensions: 149 x 311mm
 Mounting Depth: 95mm