










Although the **twenty5.21***i* is the most compact model in the new range, there's nothing small about the sound, which has the impact you'd expect from a much larger cabinet, thanks to PMC's Advanced Transmission Line technology. The speaker is ideal for use in small-to-medium listening environments where space is at a premium, but where you still want detailed bass, ultra-realistic mids and delicate highs with maximum musicality. Equally happy mounted on a stand or a bookshelf, the **twenty5.21***i* offers maximum flexibility for placement, and also makes an excellent choice for effects speakers in an immersive sound system.



Choosing the right twenty 5i model for your room size





 Freq response
 46Hz - 25kHz

 Sensitivity
 86.5dB 1W 1m

 Rec. amp power
 30 - 150W

 Effective A7L™
 1.72m
 5.6ft

Impedance 8 Ohm

Drive units LF PMC 5.5"/140mm long-throw **g-weave**[™] cone with cast alloy chassis

HF PMC/SEAS®, 19mm **twenty5i** series, SONOMEX™ fabric soft dome,

Ferrofluid cooled, with 34mm surround and dispersion grille

Crossover freq. 1.7kHz

Input connectors One pair 4mm binding posts

Dimensions H 340mm 13.4" **W** 162mm 6.4"

D 284mm 11.2" incl. binding posts (+9mm grille)

Weight 6kg 13.2 lbs ea.

Finishes Oak, Walnut, Diamond black & Silk white



twenty5

 Freq response
 39Hz - 25kHz

 Sensitivity
 89dB 1W 1m

 Rec. amp power
 30 - 200W

 Effective ATL™
 2m
 6.5ft

Impedance 8 Ohm

Drive units LF PMC 6.5"/170mm long-throw **g-weave**[™] cone with cast alloy chassis

HF PMC/SEAS®, 19mm **twenty5***i* series, SONOMEX™ fabric soft dome, Ferrofluid cooled, with 34mm surround and dispersion grille

Crossover freq. 1.7kHz

Input connectors One pair 4mm binding posts

Dimensions H 410mm 16.1" **W** 192mm 7.6"

D 373mm 14.7" incl. binding posts (+9mm grille)

Weight 10kg 22 lbs ea.

Finishes Oak, Walnut, Diamond black & Silk white

