

Tracking system	4-track, 2-channel Stereo
Head configuration	
REC/PLAY head	one each for TAPE1 and TAPE2
ERASE head	one each for TAPE1 and TAPE2
Tape speed	4.8cm/sec.
Pitch control	$\pm 12\%$ (TAPE1 PLAYBACK only)
Fast rewinding time	approximately 120 seconds (C-60 tape)
Wow and flutter	0.25% (W.RMS)
Frequency response	
Chrome tape (Type II)	30 to 15k Hz (± 4 dB)
Normal tape (Type I)	30 to 13k Hz (± 4 dB)
Total S/N ratio	59dB (at max recording level input, A-weight)

Input/Output

Analog audio input	
Connectors	RCA \times 1 pair

Nominal input level	0.28V
Input impedance	33k ohms
Mic input	
Connector	Standard 6.3mm (1/4") stereo jack
Nominal input level	0.38mV
Input impedance	3k ohms or more
Analogue audio output	
Connector	RCA × 1 pair
Nominal output level	0.46V
Output impedance	1k ohms
Headphone output	
Connector	Standard 6.3mm (1/4") stereo jack
Output power	15mW (at 32 ohms loaded)
USB digital output	
Connector	USB Type-B

Protocol	USB2.0 FULL SPEED
Sampling frequency	8k / 11.025k / 16k / 22.05k / 32k / 44.1k / 48k Hz
Bit-depth	8 / 16bit

General

Operating power	
US / Canada	AC 120V, 60Hz
UK / Europe	AC 230V 50Hz
Power consumption	22W
Dimensions	17.1"(W) × 5.7"(H) × 11.3"(D) / 435(W) × 145(H) × 285.8(D)mm
Weight	
US / Canada	9.3lbs. / 4.2kg
UK / Europe	10.2lbs. / 4.6kg
Accessories	Remote control (RC-1331), AA batteries × 2, RCA audio cable, Owner's Manual (including Warranty)

