Direct Drive Turntable System SL-1500C





Turntable Section

Туре

Direct Drive Manual Turntable

Turntable Speeds 33-1/3, 45, 78 rpm

Starting Torque 0.18 N·m / 1.8 kg·cm

Build-up Characteristics 0.7 s. from standstill to 33-1/3 rpm

Wow And Flutter 0.025 % W.R.M.S.

Turntable Platter Aluminium diecast Diameter: 332 mm Weight: Approx. 2.0 kg

(including turntable sheet)

Tonearm Section

Type

Universal Static Balance

Tracking Error Angle

Effective Length

Overhang

Within 2° 32' (at the outer groove of 30 cm (12") record) Within 0° 32' (at the inner groove of 30 cm (12") record)

Offset Angl

Arm-height Adjustment Range

0 - 6 mm

Stylus Pressure Adjustment Range

0 - 4 g (direct reading)

Head Shell Weight Approx. 7.6 g

Applicable Cartridge Weight Range

(without auxiliary weight)

5.6 - 12.0 g

14.3 - 20.7 g (including head shell)

(with auxiliary weight)

10.0 - 16.4 g

18.7 - 25.1 g (including head shell)

Head Shell Terminal Lug 1.2 mmφ 4-pin terminal lug

Terminals

Audio Output PHONO (Pin Jack) x 1

PHONO (Pin Jack) x 1
EARTH TERMINAL x 1
LINE (Pin Jack) x 1

General

Power Supply

AC 110 - 240 V, 50 / 60 Hz

Power Consumption

8 VV

Approx. 0.2 W (standby)

Dimensions (W x H x D) 453 x 169 x 372 mm

Weight

Approx. 9.9 kg

Accessories

Turntable, Turntable sheet, Dust cover, EP record adaptor, Balance weight, Auxiliary weight, Head shell, Cartridge (Ortofon 2M Red), PHONO cable,

PHONO earth lead, AC power supply cord, Owner's Manual

Panasonic Marketing Europe GmbH.

Technics is the brand name of hi-fi audio products owned by Panasonic Corporation.

The design and specification of products are constantly changing in the interest of improvement. Whilst every care has been taken in the preparation of this catalogue,

some changes may not have been indicated and may have occurred after publication.

Please check with your Panasonic dealer for details.

Panasonic Marketing Europe GmbH cannot accept any responsibility for any error or omissions.

www.technics.com

■facebook.com/technics.global

■instagram.com/technics_global

■twitter.com/technics

■youtube.com/user/TechnicsOfficial

20190418 (EU)



Direct Drive Turntable System

Premium Class SL-1500C


Rediscover Music **Technics**



The Latest Coreless Direct Drive Motor Achieves

High-precision Stable Rotation

The technologies acquired through the development of the SL-1200 Series and the high-end SL-1000R model were lavishly inserted into the motor drive unit, a key part of the turntable. The motor exclusively tunes the single-rotor, coreless direct drive motor adopted by the SL-1200GR in order to read the high rotation accuracy and high-precision signals of the record. Optimal motor control is conducted for the inertial mass of the two-layer structure platter on which the vinyl record is placed with deadening rubber on the entire back surface to eliminate unwanted resonance in the aluminium die-cast platter to eliminate the rotation irregularity called cogging. The aluminium die-cast chassis is rigidly integrated with a special material consisting of ABS mixed with glass fibre to achieve a two-layer construction. The insulator is comprised of a spring and rubber to provide optimal vibration-damping characteristics. The tonearm is a static-balance universal S-shape tonearm, another Technics tradition. By adopting a high-precision bearing using the same gimbal suspension construction and machined housing as the SL-1200 Series, high initial sensitivity is achieved. In addition, reliability has been improved by incorporating a removable power cable and gold-plated terminals, which have less sound quality degradation, for the PHONO and LINE terminals.



Complete Turntable with a Built-in Phono Equalizer and Cartridge

In order to enjoy playing analogue records more comfortably, the SL-1500C features a built-in phono equalizer and bundled cartridge. There is no need to separately prepare either one, making it easy to link with a wide range of audio equipment. The shield structure of the built-in phono equalizer suppresses the effects of external noise and noise from the power supply. It is also equipped with a switch to turn the LINE output off when it is not being used. The turntable has been designed to thoroughly shut-out adverse effects to the PHONO output. The dedicated power supply for the PHONO output terminal is isolated from the power supply for the LINE output terminal, and has been designed to prioritise sound quality by minimising the wiring of the PHONO signal. The isolated terminals also prevent wiring mistakes. An Ortofon 2M RED cartridge, which is highly acclaimed as an MM cartridge, has been selected for the bundled cartridge. Combining this high-quality cartridge with the performance of the SL-1500C will maximise the sound quality of vinyl records.



When the tonearm reaches the end of the record, the Auto Lifter function automatically raises the cartridge. This prevents unnecessary wear on your valuable vinyl records and stylus. By embedding the Auto Lifter function in the base portion of the tonearm, it eliminates impacts to the tonearm. Due to a simple design that doesn't use motor power, there is no electrical or vibrational impact and it will not prevent the movement of the tonearm. In response to requests from many users regarding the Auto Lifter function, a design that prioritises sound quality was adopted. The functions required to playback records were kept to a bare minimum, achieving simple and easy-to-use operability.

Simple Design with Functional Beauty

The SL-1500C sports a simple design without unnecessary frills, while retaining the superb operating feel that is a Technics tradition. The attractive appearance lets you enjoy playing records to your heart's content.







